

TECHNICAL DATA	STANDARD	CENTRA									
CLASSIFICATION											
Classification	EN ISO 10581	Homogeneous vinyl flooring									
	EN ISO 10874	Commercial: 34 / Industrial: 43									
Wear layer binder content	EN ISO 10581	Type I									
TECHNICAL CHARACTERISTICS											
Total thickness	EN ISO 24346	2.0 mm									
Total weight	EN ISO 23997	3000 g/m ²									
Wear layer thickness	EN ISO 24340	2.0 mm									
Surface treatment		PUR Reinforced									
Form of delivery	EN ISO 24341 Sheet (rolls)	Approx. 23 running metres x 200 cm Art. no. 21086 _ _ _ 3 digit colour number									
PERFORMANCES FOR CE MARKING REQUIREMENTS (EN 14041)											
Declaration of Performance	EN 14041	0019-0058-DoP-2018-05									
Reaction to fire	EN ISO 13501-1 EN ISO 9239-1 EN ISO 11925-2	Bfl-s1 ≥ 8 kW/m ² Pass									
Static electrical discharge	EN 1815	< 2,0 kV									
Thermal conductivity	EN 12667	Approx. 0.01 m ² K/W									
Slip resistance	EN 13896	μ ≥ 0,3									
TECHNICAL PERFORMANCES											
Residual indentation	EN ISO 24343-1	Required value: ≤ 0.10 mm Best measured value*: 0.03 mm									
Slip resistance	DIN 51130	R9									
Flexibility	ISO 24344	Pass									
Castor chair	ISO 4918	Suitable									
Light fastness	EN ISO 105-B02	≥ level 6									
Dimensional stability	EN ISO 23999	≤ 0.40%									
Chemical resistance	EN ISO 26987	Good resistance									
Bacteria resistance	ISO 846 Part C	Does not favour growth									
Underfloor heating		Suitable - max. 27°C									
Seam strength	EN 684	Average value: ≥ 240 N/50mm Individual values: ≥ 180 N/50mm									
ENVIRONMENTAL PERFORMANCES											
Total VOC emissions	ISO 16000-9	≤ 10 μg/m ³ (after 28 days)									
COLOURS											
18											
<small>The above information is subject to modification for the benefit of further improvement. (05/18) *For information - not binding. According to the European Regulation N° 305/2011 for CE Marking, the Declarations of Performance are available on our website www.polystyl-asia.com Polystyl's instructions regarding installation, cleaning and maintenance should be observed. Please contact Polystyl at the address shown for these instructions.</small>											
		CUSTOMS TARIFF : 4820 5000 00									
Centra	Welding Rod No.	Centra	Welding Rod No.	Centra	Welding Rod No.	Centra	Welding Rod No.	Centra	Welding Rod No.	Centra	Welding Rod No.
701	1287 837	732	1287 504	784	1288 339	929	1287 637	932	1287 912	972	1291 809
717	1292 383	774	1287 509	785	1287 903	930	1287 289	965	1287 638	975	1287 401
720	1287 498	783	1287 908	786	1287 771	931	1287 296	968	1287 392	976	1287 605

Printed on 100% recycled paper and cardboard - ♻️ recyclable

Centra - 21086 0208 00 - 05/18


Centra

HOMOGENEOUS COMPACT VINYL

Functional and economical flooring for demanding areas



Centra



HOMOGENEOUS COMPACT VINYL



For informations, please contact:
 sales-wa@polystyl-asia.com
 (India, Sri Lanka, Maldives, Bangladesh, Bhutan, Nepal, Pakistan)

sales-sea@polystyl-asia.com
 (Singapore, Vietnam, Cambodia, Thailand, Malaysia, Philippines, Indonesia, Myanmar, Brunei)

sales-nea@polystyl-asia.com
 (Japan, South-Korea, Taiwan, Hong Kong, Macau)

CENTRA

Calm & light pattern includes 7 fresh and neutral colours

